



3100 Peden Road Fort Worth, Texas 76179

Toll Free: (888) 876-2900

Local: (817) 236-8555

Fax: (817) 236-7212

Integral Color Admixture

- Dosage is one bag per Cubic Yard.
- Add entire bag into ready- mix truck, Mix for 120 revolutions or 10-12 minutes.
- Integral Color is a single component water-reducing admixture. (Good for color dispersion)
- Calculations for bags needed:
Take total Sq. Ft. & divide by 70 for 5" Concrete & 75 for 4" Concrete, then add 5% for waste.
- Product conforms to ASTM – C-494 & ASTM –C -979 (For Color Fastness).

Dry-Shake Color Hardener

- Product comes in 60lb. bags
- Dosage rate is approx. 60lbs. per 100 sq. ft. for earth tones or darker colors.
- Dosage rate is approx. 90lbs. per 100 sq. ft. for lighter or pastel colors.

Antiquing Release

- Product comes in 30lb. pails.
- Suggested application rate is approx. 3-4lbs. per 100 sq. ft.
- Coverage rate per 30lb pail is approx. 700-1000 depending on wind, application method, jobsite conditions, etc.
- Removal can be by two suggested methods:
 - A. By power washing
 - B. By using a detergent such as Dawn dishwashing liquid, diluted with water, and agitated at surface with medium bristle brush, followed by a light rinse with conventional water hose.

Liquid Release

- Product comes in 5 gallon pails only.
- Coverage rate per 5 gallon pails is 175 sq ft.

Overlays / Unipas Primer

- Product comes in 50lb. bags
- Product comes in standard white / gray portland cement.
- Product comes in all standard color selections per Concrete Colors Architectural Guide with a 25 bag minimum order.
- Suggested coverage rate is approx. 16-18 sq.ft. at 3/8" & 23-25 sq.ft. at 1/4" per 50lb.bag
- Suggested coverage rate for Unipas Primer is approx. 150 sq.ft. depending on the porosity of the concrete being applied.
- Unipas Primer being used as part of the mixing water, per the technical bulletin is approx. 3qts. primer and 3qts. water per 50lb. bag.
- Suggested minimum and maximum depths are: 1/4" & 1" respectively.

Chemical Stain

- Product comes in 1 & 5 Gallon containers
- Product comes in 8 standards colors.
- Color selections that are Interior only are: Avocado, St. Augustine, Cayman Blue & Liberty Rust.
- Coverage rates for **one** gallon are as follows:
 - A. Smooth troweled interior concrete is approx. 175-200 sq.ft. depending on porosity.
 - B. Broom finished exterior concrete is approx. 150-175 sq.ft. depending on porosity.
- Pricing structure same as above.
- It is highly suggested to create a pre construction mock-up prior to general application for color approval.
- Two coats of stain are suggested for most applications.

Concrete Sealers (Solvent Sealer (25%) & Natureseal HT 30%)

- Product comes in 5-Gallon pails only.
- Coverage rate is approx. 300-350 sq. ft. per gallon depending on porosity of concrete.
- Products can be used interior and/or exterior.

These are only bullets for quick answers for customers questions. Always suggest highly that they read the Technical Bulletins completely before using any of the products, as they govern the application of the products we produce.

Thanks,

Gary